



全漢企業股份有限公司  
SPI Electronic Co., Ltd.

台灣 桃園市建國東路 22 號  
NO.22,jianguo E,Rd.,Taoyuan City, Taiwan,R.O.C.  
TEL:+886-3-375-9888 FAX:+886-3-375-6966

# SPECIFICATION

## B SERIES ADAPTOR

R&D	CHECK	APPROVED	REV.
Michael	Arthur	Shipu	1.0

# Table of Content

## Section

1.0	General Description And Scope-----	(3)
2.0	Connector Pin Designations-----	(3)
3.0	Output Electrical Requirements-----	(3)
3.1	Output Rating-----	(3)
3.2	Short Circuit Protection-----	(4)
3.3	Over Current Protection-----	(4)
3.4	Turn-on Delay Time-----	(4)
3.5	Hold Up Time-----	(4)
3.6	Dynamic Load Regulation-----	(4)
3.7	Overshoot-----	(4)
3.8	Over Voltage Protection-----	(4)
3.9	Surface Temperature -----	(4)
4.0	Input Electrical Specifications-----	(5)
4.1	Input Voltage Range-----	(5)
4.2	Input Frequency-----	(5)
4.3	Inrush Current-----	(5)
4.4	Steady AC Current-----	(5)
4.5	Efficiency-----	(5)
4.6	Power Line Harmonic Requirement-----	(5)
5.0	Environmental Requirements-----	(5)
5.1	Temperature Range-----	(6)
5.2	Humidity-----	(6)
5.3	Vibration-----	(6)
5.4	Shock-----	(6)
5.5	Package Drop -----	(6)
6.0	Reliability-----	(7)
6.1	MTBF-----	(7)
6.2	Dielectric Withstand Voltage -----	(7)
6.3	Leakage Current-----	(7)
6.4	PLD-----	(7)
6.5	Electrostatic Discharge (ESD)-----	(7)

ATTACHMENT: EXTERNAL APPEARANCE

## 1.0 GENERAL DESCRIPTION AND SCOPE


This is the specification of B SERIES adaptor; AC-DC adapter switching power supply designed and manufactured by FSP GROUP, INC. located in Taiwan, Republic of China.

The specification below is intended to describe as detailed as possible the functions and performance of the subject power supply. Any comment or additional requirements to this specification from our customers will be highly appreciated and treated as a new target for us to approach.

## 2.0 CONNECTOR PIN DESIGNATIONS

The pin designations and color codes are defined as follows:

### OUTPUT POLARITY OF DC PLUG



## 3.0 OUTPUT ELECTRICAL REQUIREMENTS

### 3.1 OUTPUT RATING

Output Voltage	5V	9V	12V	15V	18V	24V	Nominal
Output Power	4.75 ~ 5.25V	8.55 ~ 9.45V	11.4 ~ 12.6V	14.25 ~ 15.75V	17.1 ~ 18.9V	22.8 ~ 25.2V	Regulation
<b>40W</b>	<b>0 ~ 5A (25W)</b>	<b>0 ~ 4.44A</b>	<b>0 ~ 3.33A</b>	<b>0 ~ 2.67A</b>	<b>0 ~ 2.22A</b>	<b>0 ~ 1.67A</b>	<b>Current</b>
	FSP025-1ADF01A	FSP040-1ADF02A	FSP040-1ADF03A	FSP040-1ADF04A	FSP040-1ADF05A	FSP040-1ADF06A	<b>Model</b>
<b>30W</b>	<b>0 ~ 4A (20W)</b>	<b>0 ~ 3.33A</b>	<b>0 ~ 2.5A</b>	<b>0 ~ 2A</b>	<b>0 ~ 1.67A</b>	<b>0 ~ 1.25A</b>	<b>Current</b>
	FSP020-1ADF01A	FSP030-1ADF02A	FSP030-1ADF03A	FSP030-1ADF04A	FSP030-1ADF05A	FSP030-1ADF06A	<b>Model</b>

The total output regulation shall be  $\pm 5\%$ , including the effects of line voltage variations, load current, ripple and noise, and the AC component of the load current. Ripple and noise measurements shall be made under all specified load conditions through a single Pole low pass filter with 20MHz cutoff frequency. Outputs shall bypass at the connector with a 0.1uF ceramic disk capacitor and a 10uF electrolytic capacitor to simulate system loading.

Ripple Noise: 300mV|, test condition: 90V/60Hz,output at Max. Current.

### 3.2 SHORT CIRCUIT PROTECTION

Output can be shorted without damage, and auto recovery.

### 3.3 OVER-CURRENT PROTECTION

Output current limit :6.2 +/- 0.5A (C. C. Mode)

### 3.4 TURN-ON DELAY TIME

The turn-on delay from application of AC input power to the establishment of rated DC power voltage should not exceed 3.0 seconds at normal line and maximum load output.

### 3.5 HOLD UP TIME

5mS minimum. Tested 115Vac input and max load at output.

### 3.6 DYNAMIC LOAD REGULATION

Output Change between 0% and 100% of full load, slew rate is 0.5 ~ 1.0A/uS.  
Frequency is 100 ~ 5 kHz, output voltage is within regulation.

### 3.7 OVERSHOOT

The output overshoot at turn-on shall not exceed 10% of normal voltage value with or without the load connected.

### 3.8 OVER VOLTAGE PROTECTION

The voltage will not exceed the upper trip limit **under internal test**.

<b>Output Voltage</b>	<b>5V</b>	<b>9V</b>	<b>12V</b>	<b>15V</b>	<b>18V</b>	<b>24V</b>
<b>Upper Trip Limit</b>	<b>7.5V</b>	<b>15V</b>	<b>18V</b>	<b>24V</b>	<b>27V</b>	<b>32V</b>

### 3.9 SURFACE TEMPERATURE

When Output at full load and ambient at 40°C, Input 115Vac/230Vac, case temperature under 78°C.

#### **4.0. INPUT ELECTRICAL SPECIFICATIONS**

##### **4.1 INPUT VOLTAGE RANGE**

PARAMETER	MIN.	NOM.	MAX.	UNITS
V-in Range	90V	115/230	264V	V-rms

##### **4.2 INPUT FREQUENCY**

47 - 63Hz

##### **4.3 INRUSH CURRENT**

(Cold start – 25 deg. C) DC full loading

100V	50 Amps
230V	100 Amps

##### **4.4 STEADY AC CURRENT**

Maximum steady state input current is less than 1.5A rms, at 100Vac input and maximum load.

##### **4.5 EFFICIENCY**

115Vac @Full Load	83% minimum
230Vac @Full Load	83% minimum

##### **4.6 POWER LINE HARMONIC REQUIREMENT**

The input current harmonic requirement shall be met with EN-61000-3-2.

## 5.0. ENVIRONMENTAL REQUIREMENTS

The power supply will be compliant with each item in this specification for the following environmental conditions.

### 5.1 TEMPERATURE RANGE

Operating	Output @ Full Load	0 to + 40 deg. C
Storage	-30 to +60deg.C	

### 5.2 HUMIDITY

Operating	8 – 80% RH, Non-condensing
Storage	8 – 80% RH, Non-condensing

### 5.3 VIBRATION

10 to 100Hz sweep at a constant acceleration of -0.5G for 10 min. for each of the perpendicular axes X, Y, Z.

### 5.4 SHOCK

Half-sine: 2ms

Storage All 6 sides; 50 to 90 in/sec in 10 in/sec increments.

Operating All sides except top; 40 to 70 in/sec in 10 in/sec increments.

No mechanical variations permitted. Electrically, the unit is capable of continuous normal operation after test completion.

### 5.5 PACKAGE DROP

Turn off system.

Follow MIL-STD-810D, 0 - 9.1kg 1m, 9.2 - 18.2kg 90cm.

10 drops: 1 corner, 3 adjacent edges of corner, 6 faces.

At random, repeat the above process 1 more time.

Note: Check for mechanical damage and functional failures.

## **6.0. RELIABILITY**

### **6.1. MTBF**

The subject adapter have a minimum predicted MTBF(BELLCORE TR-332) of 100000 hours of continuous operation at 25°C, maximum-output load, and nominal AC input voltage.

### **6.2 DIELECTRIC WITHSTAND VOLTAGE**

Primary To Secondary: 3000Vac 10mA for 1 second or 4242 VDC 10mA for 1 second.

### **6.3 LEAKAGE CURRENT**

It is refer to class I specified in IEC 60950.

The measured reading is less than 3.5mA at 240Vac 50Hz.

### **6.4 PLD**

Follow IEC801-5: L-N 1KV / 1.2\* 50uS no function error.

### **6.5 ELECTROSTATIC DISCHARGE (ESD)**

This adapter is capable to withstand ESD test voltage at any point around the enclosure as below, it is refer to IEC1000-4-2.

After applied +/- 8kV contact discharge and adapter is no function error.

After applied +/- 15kV air discharge and adapter is no function error.