



全漢企業股份有限公司
SPI Electronic Co. Ltd.

台灣 桃園市建國東路 22 號
No.22, Jianguo E. Rd., Taoyuan City, Taiwan, R.O.C.
TEL:+886-3-375-9888 FAX:+886-3-375-6966

SPECIFICATION

P.E	R/D	APPROVED	REV.
ANSON	ANSON	LJ WEI	S00

表單編號：7000P-0105



全漢企業股份有限公司

SPI Electronic Co., Ltd.

Electrical Specification

History

REV.	Description	Date	Drawn	Mechanical	Electrical	Approved
<u>S00</u>	SPEC ISSUE	Apr.10'03	Egg Guo	Grant Lu	Anson Liao	LJ Wei

MODEL NO. **FSP065-ACB**

SHEET 1 OF 8



全漢企業股份有限公司

SPI Electronic Co., Ltd.

Electrical Specification

Electrical Requirements

1. Input Characteristics:

ITEM	CONDITION	SPECIFICATION
1.1 Rated Input Voltage		100V / 240V
1.2 Input Voltage Range		90VAC to 264VAC
1.3 Input Frequency Range		47Hz to 63Hz (± 1Hz)
1.4 Input Voltage Harmonic Distortion		≤ 8%
1.5 Input Current	100Vac, 240Vac / 3.51A load	≤ 1.5A
1.6 Efficiency: (Warm up 10minutes later)	100Vac / 3.51A 240Vac / 3.51A	≥ 84% ≥ 84%
1.7 No Load Power Consumption	240Vac / 0A load	≤ 0.5W

MODEL NO. **FSP065-ACB**SHEET 2 OF 8



全漢企業股份有限公司

SPI Electronic Co., Ltd.

Electrical Specification

2. Output Characteristics:

※Measured at the end of DC cable.

ITEM	CONDITION	SPECIFICATION
2.1 Output Rated Voltage		18.5V
2.2 Output Current	at constant voltage mode	0A to 3.51A
2.3 Output Voltage Setting	at the output end of DC cable	18.5V \pm 3.5%
2.4 Output Voltage Ripple and Noise: (0.1uF Ceramic Cap. and 35V 47uF Aluminum Cap. Paralleled between the end of output cable)	90Vac / 3.51A 264Vac / 3.51A	\leq 300mVp-p
2.5 Output Overshoot Voltage:	From 65W load to no load, the output Overshoot voltage.	\leq 8% of Vo
2.6 Turn-On Delay Time:	At 100Vac / 65W load, output voltage shall remain regulation	\leq 2Sec.
2.7 Hold Up Time:	At 100Vac or 240Vac / 65W load, output voltage shall remain regulation	\geq 6 mS
2.8 Rise Time:	At 100Vac / 65W load, DC output rise time from 5% to 95% of Vo	\leq 50mS
2.9 Dynamic Load Change:	Output load step is 50% of full load, S/R=0.5A/us, frequency is 100Hz and 10KHz, the output regulation will be	18.5V \pm 3.5%

MODEL NO. **FSP065-ACB**SHEET 3 OF 8



全漢企業股份有限公司

SPI Electronic Co., Ltd.

Electrical Specification

3. Protection Characteristics:

ITEM	CONDITION	SPECIFICATION
3.1 Short Circuit Protection:	The adapter can withstand continuous short at DC output and no damage, it will enter into normal condition if the fault condition is removed.	No broken, no smoke.
3.2 Over-Voltage Protection	The adapter will enter into shut down that means no output while over voltage happened at output terminal that caused by internal fault. the output trip voltage will be less than <u>25V</u> . That might be return to normal state by AC reset, reset \leq 2 minutes.	
3.3 Over Current Protection:	The max. Output current will be 5A while output is constant resistor mode.	
3.4 Over Temperature Protection:	No deformation and no discoloration on case and will be shut down. That will be return to normal state by AC reset, reset \leq 2 minutes.	

MODEL NO. **FSP065-ACB**SHEET 4 OF 8



全漢企業股份有限公司

SPI Electronic Co., Ltd.

Electrical Specification

4. Environmental Characteristics:

ITEM	CONDITION	SPECIFICATION
4.1 Electric Fast Transients : Refer to IEC1000- 4-4 level 3	<p>Impulse: $\pm 1\text{kV}$ applied to L,N and chassis, pulse duration 50nS period 5 mintes. Input voltage 110Vac and 65 W load.</p> <p>Impulse: $\pm 2\text{kV}$ applied to L, N and chassis, pulse duration 50nS period 5 minutes. Input voltage 110Vac and 65W load.</p>	<p>Normal function error</p> <p>No damage</p>
4.2 Lightning Surge: Refer to IEC1000-4-5 level 3	<p>$\pm 1\text{kV}$ applied between line and line, pulse rise time 1.2us and duty time 50uS, 10 times test each one.</p> <p>$\pm 2\text{kV}$ applied between line and line or line and power ground (signal ground), pulse rise time 1.2us and duty time 50uS, 10 times test each one.</p>	<p>Normal function error</p> <p>No damage</p>
4.4 Electron Static Discharge: (Refer to IEC1000-4-2 Energy Storage Capacitor 150pF; Discharge Resistor 330 Ω)	<p>Air Discharge: $\pm 15\text{KV}$ min.</p> <p>Contact Discharge: $\pm 8\text{KV}$ min.</p>	<p>Normal function error</p> <p>Normal function error</p>
4.5 Cooling	Natural air cooling	
4.6 EMI: Adapter comply with the following national standards: EMI Conducted Emission EMI Radiated Emission	<p>FCC. DOCKET 20780. PART 15J. CLASS B</p> <p>CISPR22 : 1993/EN55022(1994):CLASS B</p> <p>VCCI CLASS II</p>	Test with system.
4.7 Safety conforming:	UL, c-UL, TUV/GS, NEMKO+CB	Depends on customer's requirement.
4.8 Leakage Current	<p>240Vac / 60Hz</p> <p>100Vac / 60Hz</p>	<p>$\leq 100\mu\text{A}$</p> <p>$\leq 60\mu\text{A}$</p>

MODEL NO. **FSP065-ACB**SHEET 5 OF 8



全漢企業股份有限公司

SPI Electronic Co., Ltd.

Electrical Specification

ITEM	CONDITION	SPECIFICATION
4.9 Insulation Resistance:	Between AC input and secondary applied 500Vdc for 1 minute.	$\geq 30M\Omega$
4.10 Dielectric Strength: (Hi-Pot)	Between AC input and secondary AC 3KV, test time 1 minute, and cut off current shall be less than 10mA AC 3kV, test time 1 sec. In production line	
4.11 Temperature:	Operating Storage	0 to 40°C -20 to +80°C
4.12 Humidity:	Operating Storage	20% ~ 80% 10% ~ 90%

MODEL NO. **FSP065-ACB**SHEET 6 OF 8



全漢企業股份有限公司

SPI Electronic Co., Ltd.

Electrical Specification

5. Mechanical Characteristics:

ITEM	CONDITION	SPECIFICATION
5.1 Dimension (Length x Width x Height)		114.5x49.5x29.5 mm
5.2 Adapter weight Case material		280g (typical)
5.3 Input AC socket Type		IEC 320 C6 Type
5.4 Output DC Cable Length Wire style		1800±50mm UL 1571 18AWG
5.5 Color Case DC Cable (including Molding Core)		Black Black

MODEL NO. **FSP065-ACB**

SHEET 7 OF 8