

FSP350-601UA



- Dimension : 190 x 100 x 40.5 mm
- Application : For Server & Workstation
- Watt : 350
- PFC : Active

Safety



Features

- High efficiency
- Low Ripple & Noise
- Output over voltage protection
- Short circuit protection on all outputs
- MTBF:100K hours at 25°C
- Overload protection
- Complies with EN61000-3-2
- AC input full range

Specifications

- **Hold-up time:** 18ms minimum at 115/ 60Hz;
230/50Hz
- **Temperature range:** operating 0 ~ 50 °C,
storage -20 ~ +80 °C
- **Humidity:** 5~95% RH
- **Efficiency:** 70% min., at full load
- **Inrush current:** 115V:80Amp-peak; 230V:
120Amps-peak
- **Voltage:** 100-240 VAC full range
- **Frequency:** 47 Hz to 63 Hz
- **Input current:** 6 amps maximum/115V,60 Hz.
3 amps maximum/230V,50Hz

Output

Output Voltage	Min. load	Max. load	Load Reg.	Ripple & Noise
+5Vsb	0.1A	2.0A	+5% - 4%	50mV P-P
-12V	0.0A	0.8A	+9% - 5%	120mV P-P
+12V2	1.0A	16.0A	+5% -4%	120mV P-P
+12V1	1.0A	18.0A	+5% - 4%	120mV P-P
-5V	0.0A	0.3A	+ -10%	120mV P-P
+5V	0.5A	25.0A	+5% - 4%	50mV P-P
+3.3V	0.5A	20.0A	+5% - 4%	50mV P-P

- +3.3V & +5V total output not exceed 150W
- +3.3V & +5V & +12V total output not exceed 330W

TPS Elektronik GmbH
Mönchengladbach
Fax: 02161 49526-29

Senefelderstrasse 8
Tel: 02161 49526-0 E-Mail: info@tps-elektronik.de

D-41066